Comité d'Evaluation de la Recyclabilité des Emballages papier-Carton PCNC 5.02A Stream

Paper Cardboard Packaging Recyclability Evaluation Committee

Technical Assessment

Paper recyclability evaluation

	GENERALITIES		
NC	Company	PAPTIC Ltd	
	Date of the request	March 2022	
	Product Name	Paptic© Apus Seal®	
	Market Area	Packaging material intended for the manufacture of flexible packaging for products	
	Type of packaged product	Not specified	
	PACKAGING DESCRIPTION		
	Shape	Paper sheet or rolls	
	Weight	45 g/m ²	
	PACKAGING COMPOSITION		
	Paper-cardboard	85 %	
	Plastic	0 %	
	Aluminium	0%	
	Steel	0%	
	Other	15 % (other fibers)	
	⇒ Fibrous element in majority, without wet strenght treatment.		
	REFERENT ASSESSMENT		
	N°190 _ Paptic Tringa ®		

PREREQUISITE

- The product is made of more than 50% (in weight) of paper-cardboard: this packaging therefore falls under the paper-cardboard recycling channel.
- In compliance with the general opinion concerning the impact of packaging having contained foodstuffs (AG N°2), any fragment of food pieces should be avoided within in this packaging to end up into the paper-cardboards recycling system.





IMPACTS EVALUATION

	PACKAGING		
PAPIER-CARTON YIELD	Medium		
DISSOLVED AND COLLOIDAL MATERIALS	Varnish	Ink	Adhesive
PULPING ENERGY		Ø	

Ø No impact

CEREC CONCLUSION

In reference to Paptic© Apus Seal technical assessment, the Apus Seal ® product will be well disintegrated under packaging paper-cardboard recycling conditions. The other fibers will be eliminated at the screening steps (15/100 slit)

In this context, the CEREC give a favourable assessment regarding the recyclability of Paptic© Apus Seal ®, in the 5.02 A standard in reference to the NF EN 643 in France which gathering the non-complexed paper-cardboard from the household waste channel.

This assessment is only valid for the unconverterd Paptic© Apus Seal ® as submitted to the CEREC, and doesn't prejudge the recyclability of transformed packaging made from Paptic© Apus Seal ®.

CEREC RECOMMANDATIONS

ECODESIGN : WAYS TO IMPROVE PACKAGING

The CEREC recommends to limitate the amount of the other fibers in order to improve the paper-cardboard yield, in accordance with packaging technical requirements.

ECODESIGN : RECOMMANDATIONS IN CASE OF ADDITIONNAL CONVERTING PROCESSES

This assessment applies only for unprinted and unconverted Paptic Apus Seal ® as submited to the CEREC.

Assuming that this product would be subject to additionnal transformations, the CEREC recommands :

- To avoid mineral oil-based additives, in particular inks based on mineral oil, in order to prevent contamination of the packaging recycling loop by these substances.

- To avoid the use of dark or bright ink so as not to colour the cellulose fibres during recycling and saturate the process water.

- To use classifiable (or non-fragmentable) glues or, failing that, water-soluble and waterdispersible glues

SORTING INSTRUCTIONS

The CEREC recommends to add the «TRIMAN » pictogram and another one to advise to put the packaging in the paper-cardboard collection bin in accordance with the «INFO TRI » guidelines for the french market, in case of this product is used as an household packaging.

VALIDATION



Marie DELAFALIZE





Validation date : 28/04/2022